

	Euclid 5	Euclid 5S	Beam 2	Euclid 5C	Beam 2C
Max format (portrait)	760 x 1060 mm 30 x 42"	530 x 750 mm 21 x 30"	760 x 1060 mm 30 x 42"	760 x 1060 mm 30 x 42"	760 x 1060 mm 30 x 42"
Min format (portrait)	320 x 457 mm 12.5 x 18"	320 x 457 mm 12.5 x 18"	500 x 700 mm 19.7 x 27.5"	500 x 700 mm 19.7 x 27.5"	500 x 700 mm 19.7 x 27.5"
Thickness	200-600 μ 8-24 pt.	200-600 μ 8-24 pt.	200-900 μ 8-36 pt.		
Corrugated (portrait)	-	-	Flute types N F G E Up to 2 mm 0.08"	Flute types N F G E B 1-3 mm 0.03 - 0.11"	Flute types N F G E B C Double wall EE 1-4 mm 0.03 - 0.15"
Max throughput*	2,250 B1 sph 2,750 B2 sph	2,750 sph	5,000 B1 sph	2,250 B1 sph	4,000 B1 sph
Height of feeder pile (including pallet)	1.1 m 3.6 ft	1.1 m 3.6 ft	1.1 m 3.6 ft	1.1 m 3.6 ft	1.1 m 3.6 ft **
Height of delivery pile (including pallet)	1 m 3.3 ft	1 m 3.3 ft	1 m 3.3 ft	1 m 3.3 ft	1 m 3.3 ft 1.4m 4.5 ft***
Net cutting area	740 x 1050 mm 29 x 41"	510 x 740 20.1 x 29"	740 x 1050 mm 29 x 41"	740 x 1050 mm 29 x 41"	740 x 1050 mm 29 x 41"
Gripper margin	15 mm 0.59"	15 mm 0.59"	15 mm 0.59"	15 mm 0.59"	15 mm 0.59"
LxWxH	8.6 x 2.1 x 2.3 m 28 x 7 x 7.5 ft	8.6 x 2.1 x 2.3 m 28 x 7 x 7.5 ft	8.8 x 2.15 x 2.1 m 28.9 x 7 x 6.7 ft	8.6 x 2.1 x 2.3 m 28 x 7 x 7.5 ft	8.8 x 2.15 x 2.1 m 18.9 x 2.3 x 2.7 m** 28.9 x 7 x 6.7 ft 62 x 7.5 x 9 ft**
Net weight	6,500 kg 14,330 lb	6,000 kg 13,228 lb	8,000 kg 17,637 lb	6,500 kg 14,330 lb	8,000 kg 17,300 kg** 17,637 lb 38,139 lb**
OPTIONAL MODULES					
HIDS, Highcon Integrated Digital Stripping	Option	Option	Option	Option	Option
Advanced Registration	Option	Option	Option	Option (from top)	Option
Variable Data Cutting	Option	Option	Option	Option	Option
Extractor				Option	Option
Nonstop feeder, stacker, waste removal				-	Option
CAD Light Editor	included	included	included	included	included

* Depending on layout and substrate thickness **Bottom feeder in nonstop configuration ***Nonstop configuration